



If you wish to PRINT this page, either right click and select the Print option (if your browser supports this option), or press Control + P (Windows) or Command + P (Macintosh) to open the print dialog box.

**UNIVERGE SV8300 SPECIFICATIONS**

Number of SV8300 Units and Chassis	1 Unit			2 Units	3 Units	4 Units	System Max. Stand Alone	System Max. w/Remote Link		
	1	2	3							
<b>Number of Ports</b>	96	192	288	576	864	1152	1152	2048		
<b>Outside Lines</b>										
<b>IP Lines</b>										
• IP Trunks (SIP) Channels				96			96	96	96	512
• IP Trunks (P2P) Channels				512			512	512	512	
<b>Analog/Digital Trunks</b>										
• Analog Trunks (COT)	48	96	144	288	432	488	512		512	
• T1/PRI Channels	96	192	288	512	512	512	512		512	
• BRI Channels	48	96	144	256	256	256	256		256	
<b>Terminals</b>										
<b>IP Terminals</b>										
• UNIVERGE DT700 Series	1024			1536			1536	1536	1536	1536
• Dterm IP Terminals										
• Dterm SIP/WLAN										
• Softphone										
• PS III				512			512			
• Standard SIP Terminal				512						
<b>Digital Telephones</b>										
• UNIVERGE DT300 Series	80	160	240	480	720	960	960		1536	
• Dterm Series i Terminals										
<b>Analog Telephones</b>										
• SLT (-24V)	96	192	288	576	864	1152	1152		1536	
• SLT (-48V)	24	48	72	144	216	288	288			

CLOSE WINDOW

Product details and specifications are typical and subject to change without notice.

[Terms of Use & Privacy](#)